


# Single row deep groove ball bearings



## Bearing Designation

**6044**

## Dimensions (mm)

|                    |     |
|--------------------|-----|
| d                  | 220 |
| D                  | 340 |
| B                  | 56  |
| B <sub>1</sub>     | 56  |
| r <sub>s</sub> min | 3   |

## Abutment and Fillet Dimensions (mm)

|                    |     |
|--------------------|-----|
| d <sub>a</sub> min | 233 |
| D <sub>a</sub> max | 327 |
| r <sub>a</sub> max | 2,5 |

## Basic Load Rating (kN)

|                |        |
|----------------|--------|
| C              | 230,41 |
| C <sub>0</sub> | 269,09 |

## Limiting Speed for Lubrication (min<sup>-1</sup>)

|                |       |
|----------------|-------|
| Grease Z, ZR   | 1 800 |
| Grease RS, RSR | -     |
| Oil            | 2 200 |

## Weight [kg]

15,6

## Tolerance Class

| Tolerance Class | Inner Ring       |     |                 |     |       |           |          |                |      |           |
|-----------------|------------------|-----|-----------------|-----|-------|-----------|----------|----------------|------|-----------|
|                 | Cylindrical Bore |     |                 |     |       |           |          |                |      |           |
|                 | $\Delta_{dmp}$   |     | $V_{dp}$        |     |       | $V_{dmp}$ | $K_{ia}$ | $\Delta_{B_s}$ |      | $V_{B_s}$ |
|                 |                  |     | Diameter Series |     |       |           |          |                |      |           |
|                 |                  |     | 7,8,9           | 0,1 | 2,3,4 |           |          |                |      |           |
|                 | max              | min | max             | max | max   | max       | max      | max            | min  | max       |
|                 | $\mu m$          |     |                 |     |       |           |          |                |      |           |
| P0              | 0                | -30 | 38              | 38  | 23    | 23        | 40       | 0              | -300 | 30        |
| P6              | 0                | -22 | 28              | 28  | 17    | 17        | 20       | 0              | -300 | 30        |

| Tolerance Class | Inner Ring        |     |                                |     |               |                   |     |                                |     |               |
|-----------------|-------------------|-----|--------------------------------|-----|---------------|-------------------|-----|--------------------------------|-----|---------------|
|                 | Tapered Bore 1:12 |     |                                |     |               | Tapered Bore 1:30 |     |                                |     |               |
|                 | $\Delta_{dmp}$    |     | $\Delta_{d1mp} - \Delta_{dmp}$ |     | $V_{dp}^{1)}$ | $\Delta_{dmp}$    |     | $\Delta_{d1mp} - \Delta_{dmp}$ |     | $V_{dp}^{1)}$ |
|                 |                   |     |                                |     |               |                   |     |                                |     |               |
|                 | max               | min | max                            | min | max           | max               | min | max                            | min | max           |
|                 | $\mu m$           |     |                                |     |               |                   |     |                                |     |               |
| P0 = P6         | 46                | 0   | 46                             | 0   | 38            | 30                | 0   | 46                             | 0   | 46            |

| Tolerance Class | Outer Ring     |     |                 |     |       |                                      |           |          |                                                                           |
|-----------------|----------------|-----|-----------------|-----|-------|--------------------------------------|-----------|----------|---------------------------------------------------------------------------|
|                 | $\Delta_{Dmp}$ |     | $V_{Dp}$        |     |       |                                      | $V_{Dmp}$ | $K_{ea}$ | $\Delta_{CS}, V_{CS}$                                                     |
|                 |                |     | Diameter Series |     |       | bearings <sup>2)</sup><br>with seals |           |          |                                                                           |
|                 |                |     | 7,8,9           | 0,1 | 2,3,4 |                                      |           |          |                                                                           |
|                 | max            | min | max             | max | max   | max                                  | max       |          |                                                                           |
|                 | $\mu m$        |     |                 |     |       |                                      |           |          |                                                                           |
| P0              | 0              | -40 | 50              | 50  | 30    | -                                    | 30        | 70       | Corresponds to $\Delta_{BS}, V_{BS}$<br>of the same bearing<br>inner ring |
| P6              | 0              | -28 | 35              | 35  | 21    | -                                    | 21        | 35       |                                                                           |

1) Valid in any bore radial plane

2) P0 - Valid only for bearings in diameter series 2, 3 and 4 \* P6 - Valid only for bearings in diameter series 0, 1, 2, 3 and 4

## Radial Clearance

| C2      |     | normal |     | C3  |     | C4  |     | C5  |     |     |     |
|---------|-----|--------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| min     | max | min    | max | min | max | min | max | min | max | min | max |
| $\mu m$ |     |        |     |     |     |     |     |     |     |     |     |
| 2       | 35  | 25     | 85  | 75  | 140 | 125 | 195 | 175 | 265 |     |     |

## Tolerance Symbols and Their Meaning

|                 |                                                                                                                                             |                |                                                                                                         |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------------------------------------------------------------------------------------------|
| $d$             | nominal bore diameter                                                                                                                       | $H_4$          | rated height of spherical-roller bearing                                                                |
| $d_1$           | nominal diameter of larger theoretical tapered bore diameter                                                                                | $\Delta_{Bs}$  | inner ring single width deviation                                                                       |
| $d_2$           | nominal diameter of the shaft washer of double direction thrust bearings                                                                    | $\Delta_{Cs}$  | outer ring single width deviation                                                                       |
| $\Delta_{ds}$   | deviation of single bore diameter from nominal                                                                                              | $\Delta_{Ts}$  | bearing single width deviation (total)                                                                  |
| $\Delta_{dmp}$  | mean cylindrical bore diameter deviation in single radial plane<br>(for tapered bore $\Delta_{dmp}$ is valid for theoretical bore diameter) | $\Delta_{T1s}$ | cone sub-unit effective width deviation                                                                 |
| $\Delta_{d1mp}$ | deviation of mean larger theoretical diameter of tapered bore                                                                               | $\Delta_{T2s}$ | cup sub-unit effective width deviation                                                                  |
| $\Delta_{d2mp}$ | mean shaft washer bore diameter deviation of double direction thrust bearings in single radial plane                                        | $\Delta_{Hs}$  | height deviation of single direction axial bearings from nominal value                                  |
| $V_{dp}$        | single bore diameter variation in single radial plane                                                                                       | $\Delta_{H1s}$ | height deviation of single direction axial ball bearings with sphered housing washer from nominal value |
| $V_{dmp}$       | mean cylindrical bore diameter variation                                                                                                    | $\Delta_{H2s}$ | height deviation of double direction axial bearings from nominal value                                  |
| $V_{d2p}$       | shaft washer bore diameter variation of double direction thrust bearings in single radial plane                                             | $\Delta_{H3s}$ | height deviation of double direction axial ball bearings with sphered housing washer from nominal value |
| $D$             | nominal outside diameter                                                                                                                    | $\Delta_{H4s}$ | height deviation of axial spherical-roller bearing from the rated value                                 |
| $\Delta_{Ds}$   | deviation of single outside diameter from the nominal dimension                                                                             | $C$            | outer ring nominal width                                                                                |
| $\Delta_{Dmp}$  | mean outside cylindrical surface diameter deviation in single plane                                                                         | $V_{Bs}$       | inner ring single width variation                                                                       |
| $V_{Dp}$        | single outside cylindrical surface diameter variation in single radial plane                                                                | $V_{Cs}$       | outer ring single width variation                                                                       |
| $V_{Dmp}$       | mean outside cylindrical surface diameter variation                                                                                         | $K_{ia}$       | radial runout of assembled bearing inner ring                                                           |
| $B$             | inner ring nominal width                                                                                                                    | $K_{ea}$       | radial runout of assembled bearing outer ring                                                           |
| $T$             | total nominal width of tapered roller bearings                                                                                              | $S_{ia}$       | shaft washer raceway axial runout                                                                       |
| $T_1$           | nominal effective width of cup sub-unit                                                                                                     | $S_i$          | housing washer raceway axial runout                                                                     |
| $T_2$           | nominal effective width of cone sub-unit                                                                                                    | $S_e$          | inner ring flat seat face axial runout of assembled bearing                                             |
| $H$             | rated width of unidirectional axial bearing                                                                                                 | $S_{ia}$       | outer ring flat seat face axial runout of assembled bearing                                             |
| $H_1$           | rated height of unidirectional ball axial bearing including the body ring                                                                   | $S_{ea}$       | flat seat face axial runout                                                                             |
| $H_2$           | rated height of bidirectional axial bearing                                                                                                 | $S_d$          | runout of outside cylindrical surface towards outer ring face                                           |
| $H_3$           | rated height of bidirectional axial ball bearing including body rings                                                                       | $S_D$          | runout of supporting face towards seat face for single row tapered roller bearings                      |
|                 |                                                                                                                                             | $S_s$          |                                                                                                         |