


Single row deep groove ball bearings



Bearing Designation

16076M

Dimensions (mm)

d	380
D	560
B	57
B ₁	57
r _s min	4

Abutment and Fillet Dimensions (mm)

d _a min	396
D _a max	544
r _a max	3

Basic Load Rating (kN)

C	375
C ₀	620

Limiting Speed for Lubrication (min⁻¹)

Grease Z, ZR	-
Grease RS, RSR	-
Oil	1 300

Weight [kg]

50,6

Tolerance Class

Tolerance Class	Inner Ring									
	Cylindrical Bore									
	Δ_{dmp}		V_{dp}			V_{dmp}	K_{ia}	Δ_{B_s}		V_{B_s}
			Diameter Series							
			7,8,9	0,1	2,3,4					
	max	min	max	max	max	max	max	max	min	max
	μm									
P0	0	-40	50	50	30	30	60	0	-400	40
P6	0	-30	38	38	23	23	30	0	-400	40

Tolerance Class	Inner Ring									
	Tapered Bore 1:12					Tapered Bore 1:30				
	Δ_{dmp}		$\Delta_{d1mp} - \Delta_{dmp}$		$V_{dp}^{1)}$	Δ_{dmp}		$\Delta_{d1mp} - \Delta_{dmp}$		$V_{dp}^{1)}$
	max	min	max	min	max	max	min	max	min	max
	μm									
P0 = P6	57	0	57	0	50	40	0	57	0	57

Tolerance Class	Outer Ring								
	Δ_{Dmp}		V_{Dp}				V_{Dmp}	K_{ea}	Δ_{CS}, V_{CS}
			Diameter Series			bearings ²⁾ with seals			
			7,8,9	0,1	2,3,4				
	max	min	max	max	max	max	max		
	μm								
P0	0	-50	63	63	38	-	38	100	Corresponds to Δ_{BS}, V_{BS} of the same bearing inner ring
P6	0	-38	48	48	29	-	29	50	

1) Valid in any bore radial plane

2) P0 - Valid only for bearings in diameter series 2, 3 and 4 * P6 - Valid only for bearings in diameter series 0, 1, 2, 3 and 4

Radial Clearance

C2		normal		C3		C4		C5			
min	max	min	max	min	max	min	max	min	max		
μm											
3	70	55	145	130	240	225	340	315	460		

Tolerance Symbols and Their Meaning

d	nominal bore diameter	H_4	rated height of spherical-roller bearing
d_1	nominal diameter of larger theoretical tapered bore diameter	Δ_{Bs}	inner ring single width deviation
d_2	nominal diameter of the shaft washer of double direction thrust bearings	Δ_{Cs}	outer ring single width deviation
Δ_{ds}	deviation of single bore diameter from nominal	Δ_{Ts}	bearing single width deviation (total)
Δ_{dmp}	mean cylindrical bore diameter deviation in single radial plane (for tapered bore Δ_{dmp} is valid for theoretical bore diameter)	Δ_{T1s}	cone sub-unit effective width deviation
Δ_{d1mp}	deviation of mean larger theoretical diameter of tapered bore	Δ_{T2s}	cup sub-unit effective width deviation
Δ_{d2mp}	mean shaft washer bore diameter deviation of double direction thrust bearings in single radial plane	Δ_{Hs}	height deviation of single direction axial bearings from nominal value
V_{dp}	single bore diameter variation in single radial plane	Δ_{H1s}	height deviation of single direction axial ball bearings with sphered housing washer from nominal value
V_{dmp}	mean cylindrical bore diameter variation	Δ_{H2s}	height deviation of double direction axial bearings from nominal value
V_{d2p}	shaft washer bore diameter variation of double direction thrust bearings in single radial plane	Δ_{H3s}	height deviation of double direction axial ball bearings with sphered housing washer from nominal value
D	nominal outside diameter	Δ_{H4s}	height deviation of axial spherical-roller bearing from the rated value
Δ_{Ds}	deviation of single outside diameter from the nominal dimension	C	outer ring nominal width
Δ_{Dmp}	mean outside cylindrical surface diameter deviation in single plane	V_{Bs}	inner ring single width variation
V_{Dp}	single outside cylindrical surface diameter variation in single radial plane	V_{Cs}	outer ring single width variation
V_{Dmp}	mean outside cylindrical surface diameter variation	K_{ia}	radial runout of assembled bearing inner ring
B	inner ring nominal width	K_{ea}	radial runout of assembled bearing outer ring
T	total nominal width of tapered roller bearings	S_{ia}	shaft washer raceway axial runout
T_1	nominal effective width of cup sub-unit	S_i	housing washer raceway axial runout
T_2	nominal effective width of cone sub-unit	S_e	inner ring flat seat face axial runout of assembled bearing
H	rated width of unidirectional axial bearing	S_{ia}	outer ring flat seat face axial runout of assembled bearing
H_1	rated height of unidirectional ball axial bearing including the body ring	S_{ea}	flat seat face axial runout
H_2	rated height of bidirectional axial bearing	S_d	runout of outside cylindrical surface towards outer ring face
H_3	rated height of bidirectional axial ball bearing including body rings	S_D	runout of supporting face towards seat face for single row tapered roller bearings
		S_s	